

TPC-PC156HA1

15.6" Full HD Apollo Lake Touch Panel PC

Version: 3.0




Features

- Widescreen 15.6" TFT LCD display, LED Backlit, Full HD 1920 *1080;
- Intel Apollo Lake J3455 1.5Ghz Quad-core processor;
- Multi-points (Max. up to 10 points) Projective capacitive touch, EETI controller;
- Aluminum-magnesium alloy, anodized treatment, Modular designed;
- DC 12V, with over-current, over-voltage and polarity protection;
- 2*GLAN, 6*USB, 6*COM, 1*HDMI, 1*VGA, Mic-in/Line-out;
- Fan-less & Rich IO design, Panel mount, VESA, Front IP65 protection.

Specification

Hardware & System	BIOS	SPI AMI EEL BIOS
	CPU	Intel Apollo Lake J3455, Quad-core 1.5Ghz, burst to 2.3Ghz
	Memory	SO-DIMM, Support DDR3L 1333/1600/1866 MHz, Max. up to 8GB
	Storage	1*mSATA (Optional support 1* 2.5" SATA)
	Graphic	Intel HD Graphics 500
	Network	2* Intel I211AT (Optional 3G/4G/Wi-Fi)
	Audio	On-board Realtek ACL 269 audio controller
	Expansion	1* Full size Mini-PCIe slot
	Watch dog	0~256 seconds programmable
	OS	Win10, Linux
IO interface	COM	6x RS232 (Optional support 1x RS485)
	Ethernet	2* RJ45, 10/100/1000 Mbps
	Audio	Mic-in/Line-out
	USB	4x USB3.0, 4x USB2.0
	Display	1x HDMI, 1x VGA
	Power	1x 2 pins, phenix terminal
LCD Display	Size/Type	15.6" TFT LCD
	Resolution	1920 * 1080 (Full HD)
	Brightness	450 nits
	Backlit & MTBF	LED backlit & 50 000hours
	Display area	344.16 * 193.59
	View angle	85/85/85/85
Touchscreen	Type	Projective capacitive touchscreen
	Touch points	Multi points touch, max. up to 10 points
	Durability	>100 000 000 times
	Surface hardness	Mohs 6H
	Special treatment	Anti-fingerprint (AF)
Structure	Structure and surface	Magnesium-Aluminum alloy, sand blasting, anodized treatment
	Mount method	Panel mount (Optional support VESA 75/100)
	Cooling system	Large area finned heat sink
	Overall dimension	395.6 * 247.9 * 84.0 (mm)
	Cut-out dimension	385 * 237 (mm)
	Net weight	5.0 KG
	IP protection	Front Panel IP65
	Power & Environmental	Operating temp.
Storage temp.		-30 ~ +70°C
Relative Humidity		10 ~ 95% @ 10C (Non-condensation)
Vibration		50 ~ 500 Hz, 1.5G, 0.15mm peak to peak
Shock		10G/Peak (11 ms)
Power input		DC 12V (Optional DC 9~36V)
Power consumption		Around 35W
EMC		CE/FCC Class A



Ordering info.

Part no.	Description
TPC-PC156HA1	15.6", 1920 * 1080, Intel Apollo Lake J3455, Pcap. touch, 2*GLAN, 6*USB, 6*COM, 1*HDMI, 1*VGA, Mic-in/Line-out, DC 12V
TPC-PC156HA1W	15.6", 1920 * 1080, Intel Apollo Lake J3455, Pcap. touch, 2*GLAN, 6*USB, 6*COM, 1*HDMI, 1*VGA, Mic-in/Line-out, DC 9~36V, No PSU by default
Memory	SO-DIMM, DDR3L, 2GB/4GB/8GB Memory
Storage	mSATA SSD: 32GB/64GB/128GB/256GB/512GB 2.5" SATA SSD: 256GB/512GB 2.5" HDD: 1TB/2TB/4TB
Wireless modules	Wi-Fi module, with Antenna Wi-Fi with BT integrated module, with Antenna All network 4G/LTE module, With Antenna
Power supply	60W PSU with cable (Optional for TPC-PC156HA1W)
TA-VESAB1	Additional VESA bracket for VESA mounting

Packing List

■ 1x Standard Product
■ 1x 60W PSU (Power Supply)
■ 1x Power cable & Plug
■ 8x Panel mount metal clips